


*BREAK SHARP EDGE UNLESS OTHER SPECIFIED
*未量倒角者去毛邊

PRELOAD(kgf)	_____
R.D	_____
S.F (kgf)	_____
DRAG TORQUE(Ngf-cm)	_____
LUBRICATION	OIL
DIRECTION OF TURN	RIGHT
PC DIA.	32.4
BALL DIA.	3.175
BALL TRACK FORM	GOTHIC
BACKLASH	0.07MAX
CIRCUIT	4
LEAD ANGLE	2.81°
DYNAMIC (kgf)	_____
STATIC (kgf)	_____
LEAD	5

SPEC: R32-5T4-FS1



CUSTR	UNCHAMFERED USE	<input type="checkbox"/> CO.5	<input checked="" type="checkbox"/> C1	<input type="checkbox"/> C	SCALE	1: X	DATE	12.14'98	
	ROUGH W/CFIN	W/CF	GRD	25°				6.3°	0.4g
MATERIAL	UNITOL DIMN mm				DWC	NT: SNCM220	APPD	PROCESS NO. G	
	UP	6	30	120					300
E: _____ e: _____	TO	±0.1	±0.2	±0.3	±0.4	±0.5	±0.8	±1.0	±1.5
	THREAD BALL TRACK	HRC 58 ~ 62				⊙	THREAD END ALLOWS ABOVE LENGTH OUT OF HARDNESS TOLERANCE	HIWIN® BALLSCREWS	

CUSTOMER DRAWING NO.	_____
MC TYPE	_____
ASAL TYPE	_____

* PLEASE IGNORE CHINESE CHARACTERS WHICH ARE FOR OUR REFERENCE ONLY.

DATE	MODIFICATION	APPROVED